

- Standard Features -

- Custom Options -



K Series KX080-4S3A
 *** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Eco Plus System
 Auto Idler
 Steel Track Model
 Air Conditioned ROPS/OPG (Top Guard, Level I) Cab
 Cloth Suspension Seat
 Kubota 3 Hydraulic Pump Load Sensing System
 1 Gear, 2 Variable Displacement Pumps
 All Controls Hydraulic Pilot Controls
 Two Operating Pattern Selection System
 Accumulator
 Digital Control Panel
 Attachment Flow Presets, Service Alerts
 Float Angle Blade w/ Bolt-on Cutting Edge
 360 Degree Full Rotation
 70 Degree Left, 60 Degree Right Boom Swing
 17.6 gpm Adjustable Auxiliary Hydraulics Port 1
 26.4 gpm Adjustable Auxiliary Hydraulics Port 2
 Thumb Bracket and Relief Valves
 Five Second Quick Preheat System
 Key Switch Stop System
 Half Pitch Rubber Tracks
 Self Bleed Fuel System
 Auto-Downshift Two Speed Travel System
 Swivel Negative Brake
 Travel Negative Brake
 Third Line

ENGINE

V3307 Kubota DI CRS Turbo Tier 4 Diesel Engine
 4 Cylinder, 4 Cycle
 62.3 Net HP @ 2000 rpm

OPERATIONAL DIMENSIONS

Max Digging Depth 15' 1"
 Max Digging Radius @ Ground Level 23' 6.3"
 Max Vertical Digging Depth 12' 7.6"
 Max Dumping Height 17' 2.7"

DOZER BLADE DIMENSIONS

Width 86.6"
 Height 19.7"
 Lift Above Ground 19.7"
 Drop Below Ground 19.7"

PERFORMANCE

Digging Force @ Bucket (K7432A) 19.7"
 Digging Force @ Dipper Arm 8,554 lbs.
 Travel Speed (Low) 1.7 mph
 Travel Speed (High) 3.1 mph
 Climbing Ability 36% / 20°
 Lift Capacity 6,500 lbs.
 Over Front Blade Grounded
 4.0 Ft. Load Point Height
 12.0 Ft. Load Radius

DIMENSIONS AND OPERATING WEIGHT

KX080-4S3A, Steel Tracks, Air Conditioned ROPS/OPG (Top Guard, Level I) Cab, Angle Dozer Blade
 Overall Length 21' 1.9"
 Overall Width 7' 2.6"
 Overall Height 8' 4"
 Operating Weight 19,250 lbs.*
 Ground Clearance 15.4"
 * Includes operator's weight, 175 lbs.

KX080-4S3A Base Price: \$110,650.00

| | |
|---|---------------------|
| (1) QUICK COUPLER K7402-QUICK COUPLER | \$1,601.00 |
| (1) 24" QUICK ATTACH TRENCHING BUCKET K7427-24" QUICK ATTACH TRENCHING BUCKET | \$2,205.00 |
| (1) 36" QUICK ATTACH TRENCHING BUCKET K7429-36" QUICK ATTACH TRENCHING BUCKET | \$2,679.00 |
| (1) 54" QUICK ATTACH GRADING BUCKET K7442-54" QUICK ATTACH GRADING BUCKET | \$2,597.00 |
| (1) COUNTER WEIGHT FOR KX080 K9857-COUNTER WEIGHT FOR KX080 | \$1,188.00 |
| (1) HYDRAULIC THUMB KIT K7405-HYDRAULIC THUMB KIT | \$4,190.00 |
| (1) STROBE LIGHT RTV900/RTV1140 V4218A-STROBE LIGHT RTV900/RTV1140 | \$176.00 |
| Configured Price: | \$125,286.00 |
| NJPA 070313-KBA Discount: | (\$21,298.62) |
| NJPA 070313-KBA Price: | \$103,987.38 |
| Dealer Assembly: | \$525.00 |
| Freight Cost: | \$1,210.00 |
| PDI: | \$250.00 |
| Bolt-On Rubber Pads for Steel Tracks = \$3,000.00 for 78 Pads - thru Summit Supply | \$3,000.00 |
| Labor to install = 2.5 hours @ \$100.00 per hour | \$250.00 |
| Install Hydraulic Thumb = 2.0 hours @ \$100.00 per hour | \$200.00 |
| Delivery to customers' location | \$200.00 |
| Additional Dealer Discount (3%) | (\$3,119.62) |
| Additional Kubota Discount | (\$7,279.12) |

Total Unit Price: \$99,223.64
 Quantity Ordered: 1
 Final Sales Price: \$99,223.64

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.