



Quotation for City of Sparks

Date: September 6, 2017

Quote No:606085-00

Prepared For:	Terry Shackelford	Quote No:	606085-00
	City of Sparks	iQuote No:	2230127
	225 South 21st Street	Sales Person:	Don Kittilsen
	Sparks, NV 89432-0857		don.kittilsen@turfstar.com
			(916) 861-7901

Nevada NASPO Contract Pricing; Contract No: 3114, Pricing is based on number of Traction Units purchased on a single order.

Summary

Configuration Name	Qty	Unit Price	Sub Total	Sales Tax	Total
010-GM5900 T4 Final	1	\$91,812.60	\$91,812.60	\$0.00	\$91,812.60
Totals:			\$91,812.60	\$0.00	\$91,812.60



Date: September 6, 2017

Quotation for City of Sparks

Quote No:606085-00

Configuration Product Details
010-GM5900 T4 Final

Model	Product Description	Qty	Unit Price	Extended	Sales Tax	Total
31698	GM5900 T4 Final	1	\$90,903.20	\$90,903.20	\$0.00	\$90,903.20
30552	Universal Sun Shade-Red	1	\$663.20	\$663.20	\$0.00	\$663.20
131-6691	SEAT COVER, LARGE	1	\$33.73	\$33.73	\$0.00	\$33.73
31609	GM5900 T4FINAL FLUID FIL TER MVP KIT	1	\$212.47	\$212.47	\$0.00	\$212.47
Totals:						\$91,812.60



Quotation for City of Sparks

Date: September 6, 2017

Quote No:606085-00

Standard Terms and Conditions

Prices, including all finance options, are valid for 30 days from date of quotation. Open Account Terms are N30, subject to credit approval. Used and demo equipment is in high demand and availability is subject to change. Delivery is FOB Destination, unless otherwise stated

Office Locations

Northern California:

5646 W Barstow Ave Ste 104
Fresno, CA 93722
Fax: (559) 277-7123

2438 Radley Court
Hayward, CA 94545
Fax: (510) 785-3576

11373 Sunrise Gold Circle
Rancho Cordova, CA 95742
Fax: (800) 241-1997

Southern California:

79-253 Country Club Drive
Bermuda Dunes, CA 92203
Fax: (760) 345-4297

955 Beacon Street
Brea, CA 92821
Fax: (800) 775-8873

2110 La Mirada Ste 100
Vista, CA 92083
Fax: (760) 734-4285

Pacific Northwest:

11175 SW Elligsen Way
Sherwood, OR 97140
Ph: (503) 691-0250

20224 80th Ave South
Kent, WA 98032
Fax: (253) 872-6942

2824 East Garland
Spokane, WA 99207
Fax: (509) 483-7563

TORO®

Groundsmaster® 5900/5910

LARGE AREA ROTARY MOWER

F E A T U R E S

- 192 in. (488 cm) width of cut, mows 100+ acres per day
- 3.3 L Yanmar® EPA Tier 4 Final and EU Stage IV emissions compliant turbo-diesel engine
- Full-time, bi-directional 4WD
- SmartPower™ -optimized mowing in all conditions
- CrossTrax® all-wheel drive system offers increased cross wheel traction control
- 0° uncut circle in turns
- Onboard InfoCenter™ with advisories and diagnostics for maximum uptime
- SmartCool™ auto-reversing cooling fans
- 24-volt electrical system powers cooling system
- HybridDrive™ cutting deck system delivers unmatched reliability
- 4-way adjustable seat and Air Ride Suspension
- Integrated ControlArm™ with fingertip electronic controls
- All-season safety cab with air conditioning and heater (5910)

More Parks & More Rec.

Tasked with maintaining more parks and sports fields with no additional workers or budget? Is it possible to do more with less? The Groundsmaster® 5900 Series mowers can mow over 17 acres/hour (6.87 hectares/hour) using only one operator! And to match the 16' (4.87 m) wide mowing brawn and a more fuel-efficient EPA Tier 4 Final and EU Stage IV emissions compliant Yanmar® 3.3 L engine, the Groundsmaster 5900 series is loaded with intelligence. SmartPower™ allows the operator to effortlessly maintain the correct speed for optimal cutting, while the SmartCool™ system prevents over-heating with auto-reversing the cooling fans. An onboard InfoCenter™ gives the operator a quick read on all systems and even provides assistance at the right moment. When the comfort and safety of an all season cab, the incredibly nimble handling, and tough Toro durability are added in, the new Groundsmaster 5900 series proves beyond doubt that increased efficiency and ease of operation lead to higher productivity.

[**toro.com/5900**](http://toro.com/5900)*Groundsmaster® 5900**Groundsmaster® 5910***4
TIER****SMARTPOWER**

Groundsmaster® 5900/5910 Specifications*

	GROUNDMASTER 5900, MODEL 31698 / GROUNDMASTER 5910, MODEL 31699
ENGINE	Yanmar 3.3L, EPA Tier 4 Final and EU Stage IV emissions compliant, turbocharged diesel with direct injection and electronic high-pressure common rail. 72 HP (53.7 kW) @ 2500 rpm, Torque: 206 lb.-ft. (279 N•m) @ 1625 rpm Displacement: 202 cu. in. (3.3 L).
COOLING SYSTEM	24V dual electric fan banks for separate engine radiator and hydraulic oil cooling; fan banks are variable speed, with auto-reverse feature (SmartCool™, based on coolant and oil temps), radiator is cross flow, 3 rows, 9 fins per in. (FPI). Hydraulic oil cooler is crossflow, 6 FPI. Cooling fan banks tilts away for fast, easy cleaning.
FUEL SYSTEM	Uses ultra-low sulfur diesel fuel only. Biodiesel compatible up to B20.
CAPACITIES	Fuel: 35 gal.(132L) Hydraulic: 19 gal (71.9 L). Engine Oil w/filter: 11 qt. (10.4 L). Coolant: 13.5 qt. (12.7 L) (Model 31698), 18 qt. (17 L) (Model 31699)
HYDRAULIC SYSTEM	Capacity: 19 gal (71.9 L) reservoir, Remote spin-on charge filter, Oil: Toro premium all season hydraulic fluid
TIRES/WHEELS	Front: 29x12.00-15, 6 ply rating, 32 psi; Rear: 23x10.50-12, 6 ply rating, 30 psi;
INSTRUMENTATION	Onboard LCD (InfoCenter™) display shows customizable gauges, service reminders, advisories/faults and troubleshooting assistance. Indicates fuel level, coolant temp, hydraulic oil temp, engine glow plug, low oil pressure, air cleaner restriction, 12 and 24 volt alternator voltage output, engine hours and rpm, and engine DPF regeneration.
POWERTRAIN	Full time automatic forward and reverse 4WD in low (mow) range. Front wheel drive in transport. Parallel hydrostatic, closed loop with cross wheel traction (CrossTrax™) design; traction drive pump: variable displacement piston, servo control. Front drive: 2-speed, fixed displacement high torque, low speed radial piston motors. Rear drive: single speed, fixed displacement, high torque, low speed radial piston motors. SmartPower™ feature controls traction speed to maintain optimal cutting blade speed.
ELECTRICAL SYSTEM	Main: 12 volt system; Alternator: 12V, 80 amp, supplied w/ engine Battery: 1380 CCA (2x 690 CCA), Cooling Fans, Engine/Hydraulic cooling: 24 volt system; Alternator: 24V, 105 amp w/ remote sense; Battery: 350 CCA; Disconnect ON/OFF switch for 12 & 24 volt service safety. Service: Dynamic, hydrostatic 4WD in low range. Front wheel drive braking in high range. Parking: Electro-hydraulic controlled via double-motion rocker switch. Spring applied, hydraulic released. Internal to front wheel motors. Automatically applies with engine OFF or key OFF Manual override from operator platform for servicing
PRODUCTIVITY	Infinitely variable speed. Forward speeds: mow: 0-10.8 mph (17.4 km/h) Transport: 0-20 mph (0-32.2 km/h). Reverse speeds: mow 0-5.7 mph (0-9.2 km/h), transport: 0-10.5 mph (0-16.9 km/h) transport. Speed control: Electronic, limits max speed. Maximum productivity: 20.8 acres/hr. (8.4 ha/hr). Typical productivity: 13.1 acres/hr (5.3 ha/hr)**; NOTE: For EU countries complying to ISO 5395, all speeds and mow rates should be reduced by 12%.
CONTROLS	Control arm, right armrest, travels with seat and suspension. Deck lift/lower, electrohydraulic switches. Throttle; electronic, variable. Traction pedal, electronic. Park brakes: double-motion switch. Steering; hydrostatic load sensing. Other: High/low range, PTO, cruise control, lights (31698 only), horn, key switch, wing deck transport latches (manual).
OPERATOR STATION	Operator platform: isolated rubber mounted. Seat: 4 way adjustable with vinyl (31698) or cloth (31699) cushions standard. Suspension: air-ride with 3 in. (7.6 cm) of adjustability. Steering: power and adjustable tilt. Traction Pedal: adjustable angle uses position sensor. Storage box, cup holder, and 12 volt power outlet, double USB port, standard.
STEERING	Uncut circle - 0" diameter. Turning radius - 86" (218 cm)
CAB (5910)	ROPS certified cab with heat, AC and the following standard features: climate system pressurized cab, heavy-duty pantograph front windshield wiper and washer, front windshield has 38" of visibility, interior mirror, fold away exterior side mirrors, molded front fenders, right and left doors and rear window have tinted (50%) glass, front and rear windows open, quick release window latches act as emergency exit, rubber sound isolator cab mounts and upholstered interior panels and headliner, textured neoprene floor mat, interior dome light. Power provided for optional aftermarket audio accessories. Optional road lights, rotating beacon and work lights available.
SAFETY AND LIGHTING	Standard (31698 & 31699): SMV sign rear mounted; LED brake, tail lights and flashers mounted in rear bumper; horn. ROPS Unit (31698) headlights, red and amber flashers, turn signals. Cab Unit (31699): Optional light kits, North American Road Light Kit (30706), Rotating Beacon Kit (31509), Work Light Kit (114-5610). Disconnect ON/OFF switch for 12 & 24-volt service safety.
CERTIFICATION	Meets or exceeds EU Machinery Directive (2006/42/EC); ISO 5395-2013 and ANSI B71.4-2012; ISO 21299 and SAE J1194; OSHA 29CFR1910.95 (SAEJ1175, European Directive 2000/14/EC, ISO 5395-2013); EN 55012:2007 and CISPR12. Model 31698 meets or exceeds ANSI/ASAE S279.12 (Lighting and Marking of Agricultural Equipment on Highways). Model 31699 air conditioning system meets SAE J1503, Section 8.
WARRANTY	Two year limited warranty.
VEHICLE WEIGHT (W/ FULL FLUIDS)	6,710 lbs. (3043 kg) (31698), 7,304 lbs. (3313 kg) (31699)
GROUND CLEARANCE	10.3 in. (26.1 cm)
DIMENSIONS	WIDTH: Transport: 99 in. (251 cm), Mow: 199 in. (505 cm) LENGTH: 174 in. (442 cm) HEIGHT: 85 in. (216 cm) (31698), 95 in. (241 cm) (31699) WHEELBASE: 77 in. (196 cm)

	CUTTING DECKS
TYPE	Three rear discharge rotary decks
CUTTING WIDTH	192 in. (488 cm), 57 in. (145 cm), 92 in. (234 cm), 144 in. (366 cm).
HEIGHT OF CUT	1-6 " in (2.5 – 15 cm) in 0.5 in. (1.3 cm) increments.
CONSTRUCTION	11/12 gauge high strength steel. 7-gauge, reinforcements, bullnose bumpers.
PROTECTION	Wing decks: 2 way shock absorption.
DECK DRIVE	HybridDrive™ - Hydraulic motor to spindle, remaining spindle(s), driven by "B" section v-belts.
TENSIONING	Automatic, spring loaded idlers.
SPINDLES	Shaft: 1.25" (3.2 cm) hardened steel. Housing: 9" (22.9 cm) ductile iron. Bearings: Greaseable tapered roller.
STANDARD BLADES	20" (50.8 cm), heat-treated steel blades.
OPTIONAL BLADES	Atomic™ mulching blades, flat blades.
SKIDS	4 reversible polymeric, 2 reversible steel

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

**Maximum productivity @ 10.8 mph (17.4 km/h) & 100% efficiency.
Typical productivity @ 8 mph (12.9 km/h) & 85% efficiency



TORO ACCESSORIES AND PARTS

MODEL/PART NUMBER	Description
30349	Universal Mount Sunshade – White
30552	Universal Mount Sunshade –Red
31324	Thermoplastic Windscreen Kit (GM5900). Abrasion-resistant polycarbonate windscreen (mounts to 2-post ROPS extension)
31325	Tempered Glass Windshield (mounts to 2-post ROPS extension)
31311	Wiper Kit for Tempered Glass Windshield
119-7719	Backrest Extension Kit – Fabric (GM5910)
119-7718	Backrest Extension Kit – Vinyl (GM5900)
114-5610	Work Light Kit (GM5910)
31353	2-Post ROPS Extension (GM5900) (includes sunshade)



	SNOWTHROWER ERSKINE MODEL 2000**
STAGE	2
WIDTH OF CUT	85" (216 cm)
CUTTING HEIGHT	29" (74 cm)
CUTTING EDGE	3/8" x 3" (9.5 mm x 7.62 cm) bolt-on
SKID SHOES	Adjustable
AUGER DIAMETER	16" (41 cm) open flight
FAN DIAMETER	20" (51 cm) 4-blade
CHUTE ROTATION	Hydraulic, 270°
SHEAR PROTECTION	Pressure relief
CASTING DISTANCE	Up to 30' (9.4 m)
APPROXIMATE SHIPPING WEIGHT	850 lbs. (386 kg)
HOSES	Included



	ROTARY BROOM M-B MODEL SHL***
TYPE	Windrow type, front mounted hydraulic broom with dual motors. Electric/hydraulic angling, 30° left and right.
BROOM SIZE	32" (81 cm) diameter x 60" (153 cm) wide.
BRUSH	Sectional brush with combination polypropylene/wire radial segments.
OPTIONS	Dirt Deflector, Storage Stands.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor. Information regarding non-Toro (Allied Vendor) products is included in the Toro Golf and Grounds Equipment Guide as a convenience to Toro customers. Toro does not warrant, endorse or support any products purchased from Allied vendors. Additionally, Toro shall not be responsible for any personal injury or property damage, whether direct or consequential, caused by such Allied products. Toro does not certify fit up, compatibility or functionality of Allied products.

**Manufactured by Erskine.

***Manufactured by M-B Companies, Inc. The Toro Company does not manufacture or sell the snow thrower, rotary broom, nor does Toro guarantee these accessories in any manner whatsoever.





Groundsmaster® 5900/5910 Accessories* (continued)



	TWO-POST ROPS EXTENSION SYSTEM
GM5900	Fits Model 31698
TWO-POST ROPS EXTENSION KIT	Base steel frame attached to existing ROPS and includes a white sunshade. Model 31353
EXTERIOR MIRROR	Quantity (1) Part Number 130-5448
INTERIOR MIRROR	Quantity (1) Part Number 130-5449
ABRASION-RESISTANT POLYCARBONATE WIND SCREEN	Improved resistance to golf ball impacts or vandalism. Model 31324
TEMPERED GLASS WINDSHIELD	Similar safety glass used in Toro all-season safety cabs. Model 31325
WINDSHIELD WIPER KIT FOR TEMPERED GLASS WINDSHIELD	For use with the tempered glass windshield only. Not for use with the polycarbonate wind screen. Model 31311
OPERATOR FAN & INTERIOR HEADLINER KIT	Overhead fan with adjustable speeds – mounts directly over operator. Part Number 132-3435
LED WORK LIGHT KIT	Includes 4 lights: 2 for front and 2 for rear; can also mount to Toro cabs. Model 31596
ROTATING BEACON	Breakaway mounting system. Also mounts on Toro cabs. Model 31509
SAFETY AND SECURITY CAGE	Steel mesh side cage doors that lock. Includes the abrasion-resistant polycarbonate wind screen. Part Number 132-3695
WIRE HARNESS KIT	Required for all electrical accessories such as wipers, lights and fan. Part Number 122-0729

